

RG9 Victoria Freestanding Bathing System





RL9 Bath Lift

The RG9 Victoria is a freestanding tub that allows the caregiver 360° unobstructed access to the resident. The low threshold and wide side-entry door allows easy access for residents with various degrees of mobility and the built-in contoured seat allows the resident to sit comfortably and safely in a slightly reclined position. For your dependent residents, the RG9 Victoria is specifically designed for use with the RL9 Bath Lift, which provides seamless transfers from bed-to-bath in a comfortable and safe seated position. The sleek exterior design of the RG9 Victoria bathing system will give your bathing area an upscale look.

Caregivers will enjoy the RG9 Victoria for its ease of use and the improved quality of care they can provide the resident. Featuring a full range of standard and optional features, the RG9 Victoria bathing system is designed to enhance the bathing experience for the resident.

The Rane Bathing and Accessibility product line provides a unique combination of style, ease of use, comfort, and low cost of ownership.

- 100% made in the USA. Manufactured in Sparta, TN from the highest quality components and materials.
- A "Best in Class" Warranty resulting in low cost of ownership:
 - 5 years for external finishes and composite shell
 - 3 years on all moving and stationary parts
 - Lifetime warranty on the door seal
- Full set of Standard Features including an easy-to-use control panel, thermostatic mixing valve, handheld shower wand, built-in disinfection system, analog thermometer, and 3/4" stainless steel supply lines.
- Nationwide Distribution and Customer Service.







RG9 Victoria Freestanding Bathing System

Standard Features

- Thermostatic Mixing Valve with anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- Built-in Disinfection System that is the most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection.
- Handheld Shower Wand for hair and upper body washing, which can be used at the same time the tub is filling.
- Analog Thermometer for monitoring tub-fill and shower wand temperatures.
- Lap and Shoulder Harness for resident safety.
- Secondary Door Lock to prevent accidental door opening when in use.
- 3/4" Supply Lines constructed of stainless steel.

Optional Features

 CleanRane™ Air Spa System with variable speeds that enhance the therapeutic and relaxing effects of bathing for the user.

Why CleanRane™ Air Spa System?

The CleanRane™ Air Spa System enhances the therapeutic and relaxing effects of bathing and provides a pleasant experience for the resident. Hydromassage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation. The hygienic and low maintenance CleanRane™ Air Spa System features 12 air jets with spring loaded check valves for back flow prevention, which prevents water from entering the air lines. Unlike most other whirlpool and air spa systems, the CleanRane™ Air Spa System does not allow water to enter the air lines, which can become a breeding ground for bacteria and mold. The highly efficient CleanRane™ Air Spa System simplifies disinfection and reduces the possibility of cross-contamination. The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.

TECHNICAL SPECIFICATIONS

Length:	60.75"
Width:	33"
Height (to top of console):	43" (lowest setting)
Height (to top of door):	36.5" (lowest setting)
Adjustable Leveling Legs:	2" maximum
Seat Width (interior):	25"
Seat Height:	18" (lowest setting)
Threshold Height:	11" (lowest setting)
Transfer Device Access:	5" H x 44" W
Weight Capacity (occupant):	600 lbs / 272.7 kg
Water Capacity (maximum):	52 gallons / 196.8 L
Fill Time:	3 minutes, 28 seconds
Drain Time:	2 minutes, 30 seconds
Water Supply Inlet:	3/4" diameter
Drain Size:	1.5"
Electrical Supply:	115V AC; 60Hz; 15 amp
Door Swing:	Outward
Door Configuration:	Right or Left Hinge



The wide side-entry door and unobstructed mobile lift access will allow the resident to enter and exit the bathtub safely and easily.



Easy to Use Control Panel

Warranty: 5 years for external finishes and composite shell, 3 years for all moving and stationary parts, and lifetime on the door seal. Certifications / Standards: A112.19.7-2012 / CSA B45.10-12 / UL 1795 / CSA C22.2 no. 218.2 / IAPMO Z124-2011 / CSA B45.5-11

www.ranetubs.com







